

# KES-AL900M Satin Stainless Steel

Description Securefast Fire Rated ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open – 12 & 24vDC				
Technical Featu	res			
Function & Operation	Electric Strike	Options	n/a	
Summary of Features	See advance features	Dimensions		
		Dimensions	See drawing	
		Finishes		
		Finishes Available	Stainless Steel	
Certification		BIM Assist™		
European Norm	No Harmonised European Norm			
Product Classification	n/a (No Harmonised European Norm)			
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)	BC(A)R Assist <sup>™*</sup>	:	
Certifire No.	n/a (No Harmonised European Norm)	Guarantee		1 Year
Declaration of Performance	n/a (No Harmonised European Norm)	Last Reviewed		17/08/2023
Other Test Evidence	n/a	* ROI Only		

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2024.

www.thekccgroup.com



## KES-AL900M

**Satin Stainless Steel** 

### Description

Securefast Fire Rated ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open - 12 & 24vDC





#### Features

- 1000lbs Holding Force (4448N / 434kgf)
- 12/24V AC/DC on site selectable
- AC Fail Secure only, selectable
- DC Fail Locked/Fail Unlocked selectable
- Monitored (Latch)
- Fire rated with KES-SINAL900-1/WHT Intumescent for use on 30min timber doors to EN 1634 opening inward and outward – Fire Assessment Report No WF 419607 by Warrington Fire
- Fire rated with KES-SINAL900-1/WHT Intumescent for use on 60 min timber doors to BS 476 (Report with GE Door Manufacturer)
- Long and short faceplates are included
- 10, 25 & 50mm extension lips available



#### Compatibility

- Securefast: SEU511/2/3/4, SEU771, SEU1092.2, SEU1094.2, SM1230, SLA520
- Alpro: A5245101/2/3/4, A5245701/2/3/4
- Adams Rite: AAR4710/1/2/3/400, AAR4750/1/2/3/400
- Assa: 8761/50/70

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2024.

www.thekccgroup.com



## KES-AL900M Satin Stainless Steel

### Description

Securefast Fire Rated ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open - 12 & 24vDC




## Specification Text

GENERAL ACCESS CONTROL

- · Manufacturer: Securefast
- Product reference: KES-AL900M
- $\cdot$  Type: Securefast Fire Rated ANSI Electric Strike Monitored & Site
- Selectable Fail Lock / Fail Open 12 & 24vDC
- $\cdot$  Size: See drawing
- · Material/ finish: Stainless Steel





For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2024.

www.thekccgroup.com