


Description

56 Series Surface Mounted Panic Bolt c/w top and bottom locking points



Technical Features

Function & Operation	Surface mounted push bar panic bolt for single or double door applications. Depressing the bar provides safe and speedy egress
Summary of Features	Surface mounted, non handed, fire rated for use on timber or steel doors

Options	Adjustable shoots (suffix A). Steel door fixing specify SD. Microswitch specify MS
---------	--

Dimensions

Dimensions	See drawing
------------	-------------

Finishes

Finishes Available	Silver, White or Black, Stainless Steel or Brass Effect
--------------------	---

Certification

European Norm	hEN1125:2008
Product Classification	③⑦⑥B①③②②A A
EC Certificate of Conformity No.	See DOP
Certifire No.	CF389
Declaration of Performance	DOP201
Other Test Evidence	n/a

BIM Assist™

CE

Certifire

BC(A)R Assist™*

Guarantee

10 Years

Last Reviewed	02/03/2017
---------------	------------

* ROI Only

Description

56 Series Surface Mounted Panic Bolt c/w top and bottom locking points



Specification Text

571 EMERGENCY EXIT DEVICES

- Standard: To hEN 1125.
- Emergency exit devices for locked doors on escape routes: CE marked.
- Manufacturer: KCC Group
- Product reference: KE-5620
- Type: 56 Series Surface Mounted Panic Bolt
- Material/ finish:[SPECIFY FINISH]

· Additional requirements: Certifire Approved, 10 Year Warranty

572 PERFORMANCE SPECIFICATION FOR EMERGENCY EXIT DEVICES

- Standard: To hEN 1125.
- Emergency exit devices for locked doors on escape routes: CE marked.
- Minimum classification grades:
- Category of use: 3
- Durability: 7
- Door mass: 6
- Suitability for use on fire/ smoke doors: B
- Safety: 1
- Corrosion resistance: 3
- Security: 2
- Projection of device: 2
- Type of device: A
- Field of application: A
- Material/ finish: [SPECIFY FINISH]

