



Description

57 Series Touch Bar Panic Latch



KE-400



Technical Features

Function	Exit from inside by touch bar
Equality Act	See Outside Access Device
Max Door W x H (mm)	692 to 900 x n/a
Max Door Thk (mm)	n/a
Other Door Size Options	Yes
Door Material & Style	Wooden or Steel, Single or Double
Mount Type, Locking Points	Surface, 1
Pullman Latch	No
Non Handed	Yes

Options: Microswitch, Alarm	Add Suffix MS, Add Suffix AL
Other Options	n/a
External Access Devices	409, 410EC, A411EC, CL1, CL2, CL3, CL4

Dimensions

Dimensions	653.5(L) 62(Projection)
------------	-------------------------

Finishes

Standard Colour Options	Silver, White with Green Touch Bar, Black with Green Touch Bar
RAL Colour Options	Yes
Finish Options	Stainless Steel or Brass Plated

Certification

European Norm	hEN1125:2008
Product Classification	③⑦⑥B①③②②B A
EC Certificate of Conformity No.	See DOP
Certifire No.	n/a
Declaration of Performance	DOP201
Other Test Evidence	n/a

BIM Assist™

CE

BC(A)R Assist™*

Guarantee

10 Years

Last Reviewed	06/01/2020
---------------	------------

* ROI Only

Description

57 Series Touch Bar Panic Latch



Specification Text

571 EMERGENCY EXIT DEVICES

- Standard: To hEN 1125.
- Emergency exit devices for locked doors on escape routes: CE marked.

- Manufacturer: KCC Group
- Product reference: KE-5710
- Type: 57 Series Touch Bar Panic Latch
- Material/ finish:[SPECIFY FINISH]

Additional requirements: Certifire Approved, 10 Year Warranty

572 PERFORMANCE SPECIFICATION FOR EMERGENCY EXIT DEVICES

- Standard: To hEN 1125.
- Emergency exit devices for locked doors on escape routes: CE marked.

- Minimum classification grades:
- Category of use: 3
- Durability: 7
- Door mass: 6
- Suitability for use on fire/ smoke doors: B
- Safety: 1
- Corrosion resistance: 3
- Security: 2
- Projection of device: 2
- Type of device: B
- Field of application: A
- Material/ finish: [SPECIFY FINISH]



KE-400

