

# KEM-CDVI/C3S11 Satin Anodised Aluminium

#### Description

CDVI Single Surface Magnet, 300kg - 660lbs Holding Force

Technical Features			
Function & Operation	Electromagnetic lock	Options	n/a
Summary of Features	See advanced features	Dimensions	
		Dimensions	Magnet: L250mm x W43mm x D25mm, Armature Dimensions: L185mm x W38mm x D11mm
		Finishes	
		Finishes Available	Aluminium
Certification		BIM Assist™	
European Norm	No Harmonised European Norm		
Product Classification	n/a (No Harmonised European Norm)		
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)	BC(A)R Assist™*	
Certifire No.	n/a (No Harmonised European Norm)	Guarantee	10 Years
Declaration of Performance	n/a (No Harmonised European Norm)	Last Reviewed	16/08/2021
Other Test Evidence	n/a	* ROI Only	



# KEM-CDVI/C3S11

## **Satin Anodised Aluminium**

#### Description

CDVI Single Surface Magnet, 300kg - 660lbs Holding Force



#### **Technical Characteristics**

Holding force: 300kg
Voltage: 12/24Vdc

• Current: @12Vdc = 480mA, @24Vdc = 240mA

• IP42

• Built-in electronic protection to eliminate back EMF



## KEM-CDVI/C3S11

## **Satin Anodised Aluminium**

#### Description

CDVI Single Surface Magnet, 300kg - 660lbs Holding Force



#### **Specification Text**

**GENERAL ACCESS CONTROL** 

· Manufacturer: CDVI

- Product reference: KEM-CDVI/C3S11

· Type: CDVI Single Surface Magnet, 300kg - 660lbs Holding Force · Dimensions: L250mm x W43mm x D25mm, Armature Dimensions:

L185mm x W38mm x D11mm

· Material/ finish: Aluminium