## KD-9130



## Description

KCC Overhead Door Closer

Satin Stainless Steel



₹Rcc			
Technical Features			
EN Power Size	2 to 4	Hold Open	Optional by Arm (not suitable for Fire Doors)
Width of Door (mm)	850 - 1100	Non-handed	Yes
Door Width Test Weight (Kg) - see EN1154	40 - 80	Cover	Yes
Arm Type	Standard 'V'	Application	Fig 1, Fig 61 & Fig 66
Closing Mechanism	Rack & Pinion	Dimensions	
Power Shoe Arm Bracket	Yes	Body Length (mm)	268.60
Angle of Opening	180 Degrees	Body Height (mm)	70.10
Power Adjustable by	Position on Door	Body Projection / Width (mm)	40.50
Adjustable Speed. Sweep/Latch	Yes / Yes	Finishes	
Backcheck	No	Finish without Cover	n/a
Delayed Action Adjustable	No	Finish with Cover	SSS, PSS, PB, RAL Colour
Certification		BIM Assist™	
European Norm	hEN1154	CE	
Product Classification	484113 2	Certifire	
EC Certificate of Conformity No.	2812-CPR-AD0108	BC(A)R Assist™*	
Certifire No.	CF5263	Guarantee	10 Years
Declaration of Performance	DOP001	Last Reviewed	19/07/2016
Other Test Evidence	n/a	* ROI Only	

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2024.

www.thekccgroup.com




## Description

KCC Overhead Door Closer

Satin Stainless Steel







## Specification Text

- 410 OVERHEAD DOOR CLOSERS · Standard: To BS EN 1154.
- Door closing devices to fire/ smoke control doors: CE marked.
- · Manufacturer: KCC Group
- Product reference: KD-9130
- · Type: Rack & Pinion Overhead Door Closer c/w Cover
- $\cdot$  Power size: 2 to 4
- · Other functions: n/a
- · Casing finish: [SPECIFY FINISH]
- $\cdot$  Operational adjustment:
- Variable power: Matched to size, weight and location of doors.
- Latched doors: Override latches and/ or door seals when fitted.
- Unlatched doors: Hold shut under normal working conditions.
- Closing against smoke seals of fire doors: Positive. No gaps.
- 412 PERFORMANCE SPECIFICATION FOR OVERHEAD DOOR CLOSERS · Standard: To BS EN 1154.
- Door closing devices to fire/ smoke control doors: CE marked.
- · Minimum classification grades:
- Category of use: 4.
- Durability: 8
- Door closer power size: 2/4
- Suitability for use on fire/ smoke doors: 1
- Safety: 1
- Corrosion resistance: 3
- · Type: Rack & Pinion Overhead Door Closer c/w Cover
- · Other functions: n/a
- · Casing finish: [SPECIFY FINISH]
- · Operational adjustment:
- Variable power: Matched to the sizes and weights of doors.
- Latched doors: Override latches and/ or door seals when fitted.
- Unlatched doors: Hold shut under normal working conditions.
- Closing against smoke seals of fire doors: Positive. No gaps.

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2024.

www.thekccgroup.com