KEM-CDVI/SD300M

Satin Anodised Aluminium

Description

CDVI Double Surface Magnet, 300kg - 661lbs Holding Force. Monitored



Technical Features

Function & Operation	Electromagnetic lock
Summary of Features	See advanced features

Options	n/a

Dimensions

Dimensions	Magnet: L496mm x H45mm x D26mm

Finishes

Finishes Available	Aluminium

Certification

European Norm	No Harmonised European Norm
Product Classification	n/a (No Harmonised European Norm)
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	n/a

BIM Assist™

BC(A)R Assist™*

Guarantee **10 Years**

Last Reviewed 18/02/2022

* ROI Only

For the purpose of continual product development, KCC reserves the right to change specifications without notice.
Please accept all dimensions as approximate. E&OE. © KCC Group 2026.

www.thekccgroup.com

Description

CDVI Double Surface Magnet, 300kg - 661lbs Holding Force. Monitored



Technical Characteristics

- Holding force: 2 x 300kg (661lbs)
- Voltage: 12/24Vdc
- Current: @12Vdc = 960mA (480mA per side), @24Vdc = 480mA (240mA per side)
- IP42

For the purpose of continual product development, KCC reserves the right to change specifications without notice.
Please accept all dimensions as approximate. E&OE. © KCC Group 2026.

www.thekccgroup.com

KEM-CDVI/SD300M

Satin Anodised Aluminium

Description

CDVI Double Surface Magnet, 300kg - 661lbs Holding Force. Monitored



Specification Text

GENERAL ACCESS CONTROL
· Manufacturer: CDVI
- Product reference: KEM-CDVI/SD300M
· Type: CDVI Double Surface Magnet, 300kg - 661lbs Holding Force. Monitored
· Dimensions: Magnet: L496mm x H45mm x D26mm
· Material/ finish: Aluminium

For the purpose of continual product development, KCC reserves the right to change specifications without notice.
Please accept all dimensions as approximate. E&OE. © KCC Group 2026.

www.thekccgroup.com