

KC-95/SS50EM Satin Nickel Plated

Description

Tigris ® Premium, Patented Squire Open Shackle Padlock





Technical Featu	res		
Cylinder Level	Premier 3 & 4	Clutch Function Option	n/a
No of Pins	6	Classroom Function Option	n/a
Patent Protected Key Control Until	Premier 3 - 2032, Premier 4 - 2042	Active Block Pin Security Option	Yes: Additional Side Mounted Blocking Pin. Specify ACTIVE
Multiple Key Profiles for large and/or Complex Systems	Yes: 18	Key Material	Nickel Silver for Maximum Durability & Strength
EN1303: 2005 Security Grade	6 (Highest)	Equality Act	n/a
EN1303: 2005 Durability Grade	6 (Highest)	Fixings	n/a
Kitemark Anti Manipulative Tests (inc. Anti-Bump)	Option to BS3621:2007. Specify ANTI BUMP	Dimensions	
TS007 Security Level(s)	n/a	Length A x B = C (mm)	Body - W50mm Shackle: Ø10
Protected From	Drilling & Picking	Finishes	
Construction Keyed Option	Yes - Construction Masters Negated from Cylinder at Hand Over. Specify CON.	Finishes Available	Black
		Colourmatch Option	n/a

_		_	_	_				_			
Ce	r i	ŀi	Ŧ	i	r	2	t	i	\mathbf{a}	n	

European Norm

BS EN1303:2015

Product Classification

1 6 0 B 0 C 6 B/C

EC Certificate of
Conformity No.

Certifire No.

n/a (No Harmonised European Norm)

Declaration of Performance n/a (No Harmonised European Norm)

Other Test Evidence Fire Tested. EN 1634:1. 60 Minutes
Timber. Reference 143145.

BIM Assist™

BC(A)R Assist™*

Guarantee 15 Years
Last Reviewed 22/04/2025
* ROI Only

For the purpose of continual product development, KCC reserves the right to change specifications without notice.

Please accept all dimensions as approximate. E&OE. © KCC Group 2025.



KC-95/SS50EM Satin Nickel Plated

Description

Tigris ® Premium, Patented Squire Open Shackle Padlock





Specification Text

CYLINDER LOCKS

- · Standard: To BS EN 1303
- · Manufacturer: Access 2
- Product reference: KC-95/SS50EM
- · Type: Premium, Patented Squire Open Shackle Padlock
- · Size: Body W50mm Shackle: Ø10 · Material/ finish: [SPECIFY FINISH]
- · Keying: Masterkeyed
- · Additional requirements: [SPECIFY ADDITIONAL OPTIONS]

PERFORMANCE SPECIFICATION CYLINDER LOCKS

- · Standard: To BS EN 1303 2015
- · Minimum classification grades:
- Category of use: 1
- Durability: 6
- Door mass: 0
- Suitability for use on fire/ smoke doors: B
- Safety: 0
- Corrosion and temperature resistance: C
- Key related security: 6
- Attack resistance: B/C
- · Material/ finish:[SPECIFY FINISH]
- · Keying: Masterkeyed