


Description

Securefast Fire Rated\* ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open – 12 & 24vDC. \*KES-SINAL900-1/WHT  
Intumescent Required



Technical Features

Function & Operation	Electric Strike
Summary of Features	See advance features

Options n/a

Dimensions

Dimensions See drawing

Finishes

Finishes Available Stainless Steel

Certification

European Norm	hEN14846
Product Classification	NPD A B ① ① ① NPD NPD NPD
EC Certificate of Conformity No.	See DOP
Certifire No.	n/a
Declaration of Performance	Declaration of Performance - AL900 Electric Release 7-1-22
Other Test Evidence	n/a

BIM Assist™

BC(A)R Assist™\*

Guarantee

1 Year

Last Reviewed

16/08/2024

\* ROI Only


#### Description

Securefast Fire Rated\* ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open – 12 & 24vDC. \*KES-SINAL900-1/WHT Intumescent Required



#### Features

- 1000lbs Holding Force (4448N / 434kgf)
- 12/24V AC/DC on site selectable
- AC Fail Secure only, selectable
- DC Fail Locked/Fail Unlocked selectable
- Monitored (Latch)
- Fire rated with KES-SINAL900-1/WHT Intumescent for use on 30 & 60min timber doors
- Long and short faceplates are included
- 10, 25 & 50mm extension lips available



#### Compatibility

- Securefast: SEU511/2/3/4, SEU771, SEU1092.2, SEU1094.2, SM1230, SLA520
- Alpro: A5245101/2/3/4, A5245701/2/3/4
- Adams Rite: AAR4710/1/2/3/400, AAR4750/1/2/3/400
- Assa: 8761/50/70

#### Description

Securefast Fire Rated\* ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open – 12 & 24vDC. \*KES-SINAL900-1/WHT Intumescent Required



#### Specification Text

##### GENERAL ACCESS CONTROL

- Manufacturer: Securefast
- Product reference: KES-AL900M
- Type: Securefast Fire Rated ANSI Electric Strike Monitored & Site Selectable Fail Lock / Fail Open – 12 & 24vDC
- Size: See drawing
- Material/ finish: Stainless Steel

