

Description

Abloy eff/eff ePED® Display Door Terminal in Accordance with EN13637. Includes 1386S00UP Interface



Technical Features

Function & Operation	Emergency opening panel to operate and control the electrical locking elements on escape routes
Summary of Features	See advanced features

Options	n/a
Dimensions	
Dimensions	L113 x H99 x D29
Finishes	
Finishes Available	Black

Certification

European Norm	No Harmonised European Norm
Product Classification	n/a (No Harmonised European Norm)
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	n/a (No Harmonised European Norm)

BIM Assist™

BC(A)R Assist™*

Guarantee

1 Year

Last Reviewed	01/09/2023
* ROI Only	

Description

Abloy eff/eff ePED® Display Door Terminal in Accordance with EN13637. Includes 1386S00UP Interface



Features

- Display Door Terminal in accordance with EN13637. Includes 1386S00UP Interface
- Emergency door release by pushing the display unit
- Pictogram with situational display of the operating status
- Status indication via illuminated ring
- Acoustic signaling of alarms or disruptions with the orientation signal function
- Display of the optional time delay
- Operation through touch display with authorisation code
- Configuration of the escape door system
- Operation and control of electrical locking elements on escape routes
- Inputs for connection of release from fire alarm system and for temporary release through an access control system

Technical Characteristics



- Current consumption 24VDC: 300 mA
- Control function: Yes, Hi-O technology
- Operating and display function: Yes, integrated
- Power supply: No, external power supply is necessary
- Connection: 4-wire bus
- Time delay: Yes (optional)
- Illuminated pictogram: Yes, by the integrated touch display
- Display of down counter: Yes
- Emergency Push Button: Yes, by pushing the display unit
- Control element: Code and function surface on touch display
- Initial configuration: Configuration by integrated touch display
- Required power supply: 24V ($\pm 15\%$) DC SELV
- Operating temperature range: $-10\text{ }^{\circ}\text{C} - +55\text{ }^{\circ}\text{C}$
- Area of application: Indoor use only
- Class of protection: IP30 (if completely installed)
- Installation: In DIN switch boxes $\geq 62.5\text{ mm}$ deep
- Dimensions: H113 x W99 x D29 mm (H x W x D)
- Inputs: 2
- Outputs: None
- Amount of bus addresses: 3
- Escape door terminal with bi-directional escape route: Yes
- Certified in compliance with EltVTR; DIN EN 13637:2015

Description

Abloy eff/eff ePED® Display Door Terminal in Accordance with EN13637. Includes 1386S00UP Interface

Specification Text**GENERAL ACCESS CONTROL**

- Manufacturer: Abloy eff/eff
- Product reference: KES-1386D10GBS0
- Type: ePED® Display Door Terminal in Accordance with EN13637. Includes 1386S00UP Interface
- Size: Controller L113 x H99 x D29
- Material/ finish: ABS / Black

