

Description

Abloy 24v DC Power Supply Unit Typically Used in Access Control Systems and Escape Route Systems



Technical Features

Function & Operation	Power Supply Unit
Summary of Features	See advanced features

Options	n/a
Dimensions	H68
Finishes	
Finishes Available	White

Certification

European Norm	See Electric Lock
Product Classification	See Electric Lock
EC Certificate of Conformity No.	See Electric Lock
Certifire No.	n/a
Declaration of Performance	See Electric Lock
Other Test Evidence	n/a

CE	
BC(A)R Assist™*	
Guarantee	1 Year
Last Reviewed	19/01/2024
* ROI Only	

## Description

Abloy 24v DC Power Supply Unit Typically Used in Access Control Systems and Escape Route Systems



### Features

- Power Supply Unit Typically Used in Access Control Systems and Escape Route Systems
- Top hat rail fixing



### Technical Characteristics

- Nominal power: 60 W
- Max. continuous current: 24 ... 28 VDC
- Output voltage: 24 VDC SELV
- Output current: 2,5 A
- Input operating voltage: 100-240 VAC
- Rated current consumption: 1.22/0.62 A
- Overload protection: Electronical
- Protection rating: II
- Operating temperature range: -10°C + 50°C
- Height: 68 mm
- Mounting method: Top hat rail distributor
- Class of protection: IP 20
- Material housing: Plastic
- Approval DIN EN 60335-1: Yes
- Approval DIN EN 62368-1: Yes

### Description

Abloy 24v DC Power Supply Unit Typically Used in Access Control Systems and Escape Route Systems



### Specification Text

#### ACCESS CONTROL

- Manufacturer: Abloy
- Product reference: KEL-1003
- Type: Abloy 24v DC Power Supply Unit Typically Used in Access Control Systems and Escape Route Systems
- Material/ finish: White
- Additional requirements: n/a