

Description

Abloy Lead Cover 330mm (for Hollow or Pivot Hung Doors) with Integrated Break-Proof Flex Cable & 10-pin Clamp-plug Connection Technology



Technical Features

Function & Operation To Transfer Data & Power from the Door Frame to the Door

Summary of Features See advanced features

Options n/a

Dimensions

Dimensions L297mm x W24mm x D127

Finishes

Finishes Available Satin Chrome

Certification

European Norm See Electric Lock

Product Classification See Electric Lock

EC Certificate of Conformity No. See Electric Lock

Certifire No. n/a

Declaration of Performance See Electric Lock

Other Test Evidence n/a

CE

BC(A)R Assist™*

Guarantee

1 Year

Last Reviewed

19/01/2024

* ROI Only

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2025.

Description

Abloy Lead Cover 330mm (for Hollow or Pivot Hung Doors) with Integrated Break-Proof Flex Cable & 10-pin Clamp-plug Connection Technology



Features

- Lead cover for concealed mounting
- With integrated break-proof flex cable, 10-pin clamp-plug connection technology and installation casing on both sides
- Installation system for minimal chamber dimensions and unobstructed movement
- This system is particularly suitable for door systems with reduced spacing for hinges and inside hinges
- The particular advantage of this mounting type is being able to position the casing practically flush with the frame (<1 mm distance when door is closed)
- Minimal gaps for door rotation, as with inside hinges, for instance, do not result in the door jamming



Technical Characteristics

- Contact resistance per signal: 0.21 Ohm
- Input operating voltage: 24 V +20%
- Max. current consumption: 1A 100% ED, 4 A max. 1 sec. 10% ED
- Version: Plug-in device
- Version: Installation casing on both sides
- Material installation casing: Stainless steel
- Material spiral hose: Stainless steel
- Max. permissible horizontal rotation: 100 mm
- Cycles at 180 turns: 1,000,000
- Area of application: Installation system for minimal room dimensions and unobstructed movement
- Signal transmission: 10-pin

Description

Abloy Lead Cover 330mm (for Hollow or Pivot Hung Doors) with Integrated Break-Proof Flex Cable & 10-pin Clamp-plug Connection Technology



Specification Text

ACCESS CONTROL

- Manufacturer: Abloy
- Product reference: KEL-10314-14-10--00
- Type: Abloy Lead Cover 330mm (for Hollow or Pivot Hung Doors) with Integrated Break-Proof Flex Cable & 10-pin Clamp-plug Connection Technology
- Material/ finish: Satin Chrome
- Additional requirements: n/a