

**Description**

Abloy Top Locking Rod for Security Top Lock N5120 and Passive Leaf Lock N1940 x 1000mm (N51210510000000)



**Technical Features**

Function & Operation      Top Locking Rod  
 Summary of Features      Compatible with N5120 and N1940

Options      N51210515000000: Length 1500 mm

**Dimensions**

Dimensions      L1,000mm

**Finishes**

Finishes Available      Stainless Steel

**Certification**

European Norm      See Abloy Passive Leaf Lock  
 Product Classification      See Abloy Passive Leaf Lock  
 EC Certificate of Conformity No.      See Abloy Passive Leaf Lock  
 Certifire No.      n/a  
 Declaration of Performance      See Abloy Passive Leaf Lock  
 Other Test Evidence      n/a

**BC(A)R Assist™\***

**Guarantee**

**1 Year**

Last Reviewed      19/01/2024

\* ROI Only

*For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2025.*

**Description**

Abloy Top Locking Rod for Security Top Lock N5120 and Passive Leaf Lock N1940 x 1000mm (N51210510000000)

**Specification Text**

571 EMERGENCY EXIT DEVICES

- Standard: To BS EN 179.
- Emergency exit devices for locked doors on escape routes: CE marked.
- Manufacturer: Abloy
- Product reference: KEL-N5121
- Type: Abloy Top Locking Rod for Security Top Lock N5120 and Passive Leaf Lock N1940 x 1000mm (N51210510000000)
- Material/ finish: Stainless Steel
- Additional requirements: None

