


Description

KCC Premium, Restricted Single & Turn Cylinder 3030



Technical Features

Cylinder Level	Restricted	Clutch Function Option	No
No of Pins	6	Classroom Function Option	No
Patent Protected Key Control Until	n/a	Active Block Pin Security Option	No
Multiple Key Profiles for large and/or Complex Systems	No	Key Material	Plated Brass
EN1303: 2005 Security Grade	6 (Highest)	Equality Act	n/a
EN1303: 2005 Durability Grade	6 (Highest)	Fixings	M5 x 70 Retaining Screw
Kitemark Anti Manipulative Tests (inc. Anti-Bump)	n/a	D i m e n s i o n s	
TS007 Security Level(s)	n/a	Length A x B = C (mm)	32.5 x 32.5 = 65
Protected From	Picking	F i n i s h e s	
Construction Keyed Option	No	Finishes Available	Satin Nickel 02, Polished Brass 20
		Colourmatch Option	No

Certification

European Norm	BS EN1303:2005
Product Classification	①⑥⑦①⑦C⑥⑦
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	n/a

BIM Assist™

BC(A)R Assist™*

Guarantee

2 Years

Last Reviewed

05/08/2016

* ROI Only

*For the purpose of continual product development, KCC reserves the right to change specifications without notice.
Please accept all dimensions as approximate. E&OE. © KCC Group 2025.*

www.thekccgroup.com

Description

KCC Premium, Restricted Single & Turn Cylinder 3030

**Specification Alert**

The following guidelines are provided so as to explain the security and capacity differences between KCC Restricted and KCC Patented master keyed Cylinders. If in doubt please contact our office for further details.

Protection against Unauthorised Key Duplication

- **PATENTED:** Extensive protection with legal recourse against those that sell pirate keyblanks
- **RESTRICTED:** Limited and no legal recourse against pirate blanks

Master Key System Complexity & Size

- **PATENTED:** Large & complex systems
- **RESTRICTED:** Sub Masters and differs per sub master, select ONE scenario from the following (note common entrance keying will significantly reduce the following) :
 - Master, 2 sub masters, 325 differs
 - Master, 4 sub masters, 250 differs
 - Master, 6 sub masters, 100 differs
 - Master, 10 sub masters, 80 differs

Description

KCC Premium, Restricted Single & Turn Cylinder 3030



KC-9410

Specification Text

CYLINDER LOCKS

- Standard: To BS EN 1303
- Manufacturer: KCC Group
- Product reference: KC-9410
- Type: Premium, Restricted Single & Turn Cylinder
- Size: 32.5/32.5 65mm Length
- Material/ finish: [SPECIFY FINISH]
- Keying: Masterkeyed
- Additional requirements: [SPECIFY ADDITIONAL OPTIONS]

PERFORMANCE SPECIFICATION CYLINDER LOCKS

- Standard: To BS EN 1303
- Minimum classification grades:
- Category of use: 1
- Durability: 6
- Door mass: 0
- Suitability for use on fire/ smoke doors: 1
- Safety: 0
- Corrosion and temperature resistance: C
- Key related security: 6
- Attack resistance: 0
- Material/ finish:[SPECIFY FINISH]
- Keying: Masterkeyed

