

KDO-S/QUADRA/NFR

White

Description

KCC Quadra Steel Riser Door System c/w Three Point Locking and Top and Bottom Pivot. Non Fire Rated





Product Summary

Quadra is a concealed frame riser door system designed to semi-conceal unsightly riser and service doors. The system includes a steel frame and steel door leaves

Certification		BIM Assist™	
European Norm	No Harmonised European Norm		
Product Classification	n/a (No Harmonised European Norm)		
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)	BC(A)R Assist™*	
Certifire No.	n/a (No Harmonised European Norm)	Guarantee	1 Year
Declaration of Performance	n/a (No Harmonised European Norm)	Last Reviewed	23/08/2019
Other Test Evidence	Acoustic Report BMT MTP F14387 02 Rev1	* ROI Only	

For the purpose of continual product development, KCC reserves the right to change specifications without notice.

Please accept all dimensions as approximate. E&OE. © KCC Group 2025.



KDO-S/QUADRA/NFR

White

Description

KCC Quadra Steel Riser Door System c/w Three Point Locking and Top and Bottom Pivot. Non Fire Rated







- Concealed frame riser door system designed to semi-conceal unsightly riser & service doors
- Pivot hinge ensures that the door is easy to hang
- Supplied to site as an integral, four sided frame and door system, preconstructed to form a robust unit
- The doorset is then fixed into the shaft/partition wall through the perforated flange and fixing holes in the face of the frame. Once in place, Quadra offers excellent accessibility combined with solid durability
- Once in place, Quadra can be plastered or tape and jointed up to the integral stop-beads at the corners of the frame, creating a perfectly flush profile with the wall
- Intumescent mastic used at the back of the frame to structural opening
- The system can then be painted with the same finish as the surrounding wall, creating a consistent, high-quality aesthetic finish that sets the project apart
- Air leakage performance class 2 (300Pa)



Technical Characteristics

- Configuration: Supplied as single, double, triple or multiple leaves (up to a maximum of 6 leafs with a 1000mm maximum leaf width)
- Door Size: Custom up to 1900mm wide (double door) and 3000mm high.
 44mm wide and 90mm wide when acoustic ratings above 39dB is required
- Frame material: 1.2mm cold rolled mild steel / folded zinc plated steel
- Door material: 1.2mm steel facade with insulated core
- Specify finishes: Primed and textured for site painting or powder coated to standard RAL colour
- Specify lock: 3 point locking with square drive key (standard) or Euro cylinder provision
- Handing: Specify RH or LH for single door. Specify RH active or LH active for double door
- Specify frame: Concealed or visible, 4 side or flat bottom threshold (see frame options)



Fire & Smoke Rating

- There are three levels of fire rating available:
 - NFR: Non fire rated
 - FD60S: Tested in accordance with BSEN 1634-1: 2014 & BSEN1363-1:
 2012. Report WF BMT/CNA/F15212 available on request
 - FD120S: Tested in accordance with BSEN 1634-1: 2014 & BSEN1363-1: 2012. Report WF BMT/CNA/F15212 available on request



KDO-S/QUADRA/NFR White



Acoustic Rating Options

- The acoustic capability is as follows:
 - 35 dB Rw Standard
 - 36 dB Rw Up to 6 leaves
 - 39 dB Rw Up to 6 leaves
 - 44 dB Rw Double leaf only
 - 46 dB Rw Single leaf only



Locking Options

- 3 point locking solutions, select options of:
 - Square key drive
 - Euro profile cylinder (when extra security is required). Please note that when specifying this option, the cylinder must be ordered separately.
 - Concealed locking cover (see illustration)





Frame Options

- Concealed Frame 4 sided: The most popular version, the four sided concealed frame allows you to fully conceal your frame providing an almost completely hidden doorset
- Concealed Frame 3 sided: As the above but with a flat bottom threshold (used in conjunction with a skirting board to give a shadow gap detail)
- Visable Frame: Where aesthetics are not so key or you may wish to install the
 doorset after the after the tape and jointing / plastering. The Quadra can be
 provided with a visable frame that is surface mounted and on top of the wall
 surface



KDO-S/QUADRA/NFR White



Sectional View

• Supplied to site as an integral, four sided frame and door system, preconstructed to form a robust unit



Finishes

Door/panel Leaf Construction and finishes: Powdercoated in textured finish for on-site painting. Powdercoated in smooth finish, 30% sheen to RAL colour



KDO-S/QUADRA/NFR

White

Description

KCC Quadra Steel Riser Door System c/w Three Point Locking and Top and Bottom Pivot. Non Fire Rated





Specification Text

· Product Name: KDO-SEL/QUADRA/NFR

· Manufacturer: KCC Group

· Door Size: Custom. As per door schedule

 \cdot Frame material: 1.2mm cold rolled mild steel / folded zinc plated steel

· Door material: 1.2mm steel facade with insulated core

 \cdot Door thickness: 44mm, 90mm (when acoustic ratings above 39db are required)

· Frame type: Concealed, Picture frame, Flat threshold [SPECIFY]

· Finishes: Powdercoated in textured finish for onsite painting, Powdercoated in smooth finish 30% sheen, RAL Colour [SPECIFY]

· Hinges: Pivot

 $\cdot Locks/Latches: 3\ Point\ Lock\ c/w\ Square\ Key\ Drive/\ Option\ of\ Euro\ Cylinder\ [SPECIFY]$

· Fire Rating: NFR

 \cdot Acoustic Rating: Not required / 30db / 36db / 39db / 42db [SPECIFY]

