


**Description**

KCC Surface Standard Single Magnet, Monitored, 1200lbs Holding Force (A10020)



**Technical Features**

Function & Operation	Electromagnetic lock
Summary of Features	Holding force of up to 1200lbs (545kg), site selectable 12 or 24v DC, status LED lights, aluminium housing, current draw 500mA @ 12vDC & 250mA @ 24vDC. Operating temperature -10 to 55 degrees C

Options Door Status Monitoring (DS)

**Dimensions**

Dimensions Magnet: L265 x W67 x D40, Armature Plate: L185 x W61 x D16, Mounting Plate: L265 x W40 x D6

**Finishes**

Finishes Available Brushed Aluminium

**Certification**

European Norm	No Harmonised European Norm
Product Classification	n/a (No Harmonised European Norm)
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	EN1634 Fire Assessed Report 400128

**BIM Assist™**

**BC(A)R Assist™\***

**Guarantee**

**1 Year**

Last Reviewed

05/08/2016

\* ROI Only

For the purpose of continual product development, KCC reserves the right to change specifications without notice. Please accept all dimensions as approximate. E&OE. © KCC Group 2026.

## Description

KCC Surface Standard Single Magnet, Monitored, 1200lbs Holding Force (A10020)



## Specification Text

### GENERAL ACCESS CONTROL

- Manufacturer: KCC Group
- Product reference: KEM-600M
- Type: Slimline Single Magnet, holding force up to 1200lbs (545kg), Monitored
- Size: Magnet: Magnet: L265 x W67 x D40, Armature Plate: L185 x W61 x D16, Mounting Plate: L265 x W40 x D6
- Material/ finish: Brushed Aluminium

