

Fire Rated, Satin Anodised Aluminium

Description

GEZE Drive System for Automatic Folding Doors - Fire Rated







Product Summary

The GEZE Slimdrive SF-FR is an electro-mechanical drive system for automatic folding doors, Internal or external - fire rated

Certification		BIM Assist™	
European Norm	EN16005	CE	
Product Classification	Complies or exceeds the design guidelines as depicted		
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)	BC(A)R Assist™*	
Certifire No.	n/a	Guarantee	1 Year
Declaration of Performance	n/a (No Harmonised European Norm)	Last Reviewed	20/12/2019
Other Test Evidence	n/a	* ROI Only	

For the purpose of continual product development, KCC reserves the right to change specifications without notice.

Please accept all dimensions as approximate. E&OE. © KCC Group 2025.

www.thekccgroup.com



Fire Rated, Satin Anodised Aluminium

Description

GEZE Drive System for Automatic Folding Doors - Fire Rated





Features

- The GEZE Slimdrive SF-FR is an electro-mechanical drive system for automatic folding doors, Internal or external - fire rated
- Overall height of only seven centimetres allows large passage heights
- Automatic adaptation to traffic flow where for example, the door adjusts its door hold open time to a longer time in busy periods and a shorter time in quiet periods
- · Automatic reversal when an obstacle is detected
- Site selectable programming options via the Display Programming Switch (DPS) include:
 - Automatic mode: The doors will automatically power open on entry or egress via the activation devices, and automatically close after a preset time
 - Pharmacy opening: The doors can be programmed to have a limited width opening at certain times (staff opening up time etc.)
 - Shop closing mode: Exit only, traffic can flow in one direction only
 - Locked shop closing: As above, with a locking motor variant to prevent the door being manually opened from the outside. This is a motor upgrade
 - Night mode: Door is closed and locked (where applicable). May be overridden by a keyswitch for example
 - Hold open mode: This mode will drive the doors to the open position and maintain them in this position until another function is selected. This is commonly used on hot days
 - Automatic opening in the event of a power failure
 - Automatic opening in the event of a fault
- Electro-magnetic, b-stable, tooth belt locking design ensures that the doors remain in a secure locked position even in the event of a power failure



Fire Rated, Satin Anodised Aluminium



Technical Characteristics

• Dimensions: H70mm x D282mm

Scope: 4 leaf door systems

• Opening Width 4-leaf: 900mm - 2000mm

Leaf Weight 4-leaf: 40kg

· Motor Type: Gear, two motors provided

Motor Torque: 400 Ncm

Opening/Closing Speed (Max.): 0.8/0.8 m/s

Hold Open Time: 0 - 60s

Adjustable Opening/Closing Force (Max.): 150N

· Locking: Toothed belt locking, electro magnetic, bi-stable

Power

Voltage: 230V

Frequency: 50 – 60 Hz

Capacity Rating: 140 W

Disconnection from Mains: Main switch in the drive

Rechargeable Battery: NiCd, 24 V, 700 mAh

Power Supply for Peripherals: Yes

• Door Leaf Adjustment Vertical: 10mm

• Door Leaf Adjustment Horizontal: 6mm

· Anti-tilt Protection: Standard

Self Cleaning: Yes

Control Unit (DCU1-NT)

Fault Memory: Yes

Statistical Data Memory: Yes

Software Updates: Yes

o Optional BUS Interface: Yes

Connection for Fire Alarm System: Yes

Programmable Inputs: 3

Programmable Outputs: 2

• Temperature Range: -15 to +50 °C

IP Rating: IP20

Automatic Opening in the Event of a Power Failure: Adjustable

Automatic Closing in the Event of a Power Failure: Adjustable

 Function in the Event of a Power Failure: Adjustable. Battery backup would allow for up to 30 min./ 30 cycles

Automatic Opening in the Event of a Fault: Not available



This product meets / surpasses the following:

- DIN 18650: The industrial standard DIN 18650 was created to guarantee operators and users of automatic doors optimum safety. GEZE sliding door systems have been type-tested and certified in accordance with DIN 18650.
- EN 16005: The European standard EN 16005 sets out the design requirements and testing methods used to ensure the safe use of automatic doors. All automatic door systems and safety sensors from GEZE meet the EN 16005 standard
- DIN EN ISO 13849: Performance Level D
- EN 61000-6-2:2005/AC:2005
- EN 61000-6-3:2007/A1:2011/AC:2012
- EN 60335-1:2012/AC:2014
- EN 60335-2-103:201



For the purpose of continual product development, KCC reserves the right to change specifications without notice.

Please accept all dimensions as approximate. E&OE. © KCC Group 2025.




Fire Rated, Satin Anodised Aluminium

Description

GEZE Drive System for Automatic Folding Doors - Fire Rated





DOOR AUTOMATION

- · Manufacturer: Geze
- Product reference: KAD-SLIMDRIVE SF-FR
- \cdot Type: Drive System for Automatic Folding Doors Fire Rated
- · Finish: [SPECIFY]



