


Description

KCC Surface Slimline Single Magnet 600lbs Holding Force (A10001)



Technical Features

Function & Operation	Electromagnetic lock
Summary of Features	See advanced features

Options	Monitored (M) or Magnetic Bond Sensor (MBS)
---------	---

Dimensions

Dimensions	Magnet: L250 x W42 x D26, Armature Plate: L179 x W38 x D11
------------	--

Finishes

Finishes Available	Brushed Aluminium
--------------------	-------------------

Certification

European Norm	No Harmonised European Norm
Product Classification	n/a (No Harmonised European Norm)
EC Certificate of Conformity No.	n/a (No Harmonised European Norm)
Certifire No.	n/a (No Harmonised European Norm)
Declaration of Performance	n/a (No Harmonised European Norm)
Other Test Evidence	EN1634 Fire Assessed Report 400128

BIM Assist™

BC(A)R Assist™*

Guarantee

1 Year

Last Reviewed

17/04/2020

* ROI Only

Description

KCC Surface Slimline Single Magnet 600lbs Holding Force (A10001)

**Technical Characteristics**

- Holding force of up to 600lbs (272kg)
- Site selectable 12 or 24v DC
- Aluminium housing
- Voltage tolerance $\pm 15\%$
- Current draw 500mA @ 12vDC & 250mA @ 24vDC (at 20°C)
- Operating temperature -10 to 55°C
- Lock's surface temperature = current temperature $\pm 20\%$ (when power is on)
- Humidity 0-95% non-condensing
- Weight of 2kg (approx.)

Description

KCC Surface Slimline Single Magnet 600lbs Holding Force (A10001)



Specification Text

GENERAL ACCESS CONTROL

- Manufacturer: KCC Group
- Product reference: KEM-300
- Type: Slimline Single Magnet, holding force up to 600lbs (272kg)
- Size: Magnet: L250 x W42 x D26, Armature Plate: L179 x W38 x D11
- Material/ finish: Brushed Aluminium

